
Boca Systems Lemur-C

Solutions for the Ticketing Industry







General

Print Method: direct thermal PrintSpeed: 8" per sec. maximum **Resolution:** 203 dpi (8 dots/mm) Size: 6.5 H x 6.6 W x 6.7 L

Weight: 4 pounds

Media Transport

Media Type: internal roll Ticket Thickness: .002" to .004"

Ticket Width: 80 mm

Ticket Separation: cutter (horizontal)

Interfaces

Standard: Serial and USB

Optional: Ethernet, Bluetooth & Wi-Fi

Protocols

Standard: FGL

Drivers: Windows, Mac and Linux

Approvals

UL / FCC / CE / CCC

* Print speed may be affected at extreme tempuratures

Power Requirements

100-240 VAC, 50/60Hz, 65W max Amp max 24 V DC, 2.5 Amp max

Environmental

* Operating Temperature: -20 to 60°C **Relative Humidity:** 10% to 90% Storage Temperature: -40 to 70°C above specs without condensation

Bar Codes

Most 1D and 2D codes including PDF417, DataMatrix, QR, Aztec

Full speed printing of picket fence and ladder bar codes

Fonts

Resident fonts: 16 bitmapped fonts (including Cyrillic and German characters) and Asian character sets (optional) Downloadable fonts: HP Soft fonts /

TrueType fonts

Downloadable RAM: up to 27MB

Downloadable Flash: up to 12MB (optional)

Graphics

FGL format, PCX format (1bit b/w), BMP format (1bit b/w)

Web Interface (ethernet only)

Real-time status monitor Email notification

Projected Life

Cutter: 1 million cuts

Print Head: 100 km of paper or 100 million dot activations

Bonus: Free print head replacements when exclusively using Boca paper

Warranty

Printer: 1 year, parts and labor

Print head: 90 days

Patents: BOCA has a patented head protection system that prevents premature

head failure



